

Al vezne čaure za gnječenje

Koriste se za spajanje Al provodnika istog preseka, metodom šestougaonog presovanja, spoj prema SRPS N.F4.101. Preporučujemo presovanje FEMAN presama tipa.

Kodni broj	Oznaka mm ² /Vijak M	d1 mm	d2 mm	L mm	Broj presovanja meh./hidr.	Pakovanje kom	Težina g/100kom
2100016	FAC-16	11,0	5,5	53,0	3-3/-	300	1,09
2100025	FAC-25	12,0	6,5	53,0	3-3/-	200	1,20
2100035	FAC-35	14,0	8,0	57,5	3-3/2-2	100	1,75
2100050	FAC-50	15,6	9,3	66,5	4-4/2-2	100	2,11
2100070	FAC-70	18,0	11,2	70,0	4-4/2-2	100	3,07
2100095	FAC-95	22,0	12,5	87,0	5-5/3-3	100	6,41
2100120	FAC-120	22,0	15,0	104,0	6-6/3-3	100	6,00
2100150	FAC-150	25,5	16,5	117,0	6-6/3-3	100	9,00
2100152	FAC-185	28,0	18,3	123,0	6-6/3-3	50	11,70
2100240	FAC-240	32,0	21,0	14,0	7-7/3-3	25	16,17
2100300	FAC-300	40,0	23,5	140,0	7-7/3-3	10	22,50

