

WA\_5G1504



WA\_5G1504



## Otporni na udarne struje do 250 A



• Tip AC – osetljivi na diferencijalne AC

• Bez vremenskog kašnjenja – otporni na udarne struje do 250 A

$I_{tr,sn}$ [A]	Oznaka tipa	Kat. broj	Kom. u pakovanju
<b>2-polni</b>			
25/0.03	PF6-25/2/003	286492	1/60
25/0.10	PF6-25/2/01	286493	1/60
25/0.30	PF6-25/2/03	286494	1/60
25/0.50	PF6-25/2/05	286495	1/60
40/0.03	PF6-40/2/003	286496	1/60
40/0.10	PF6-40/2/01	286497	1/60
40/0.30	PF6-40/2/03	286498	1/60
40/0.50	PF6-40/2/05	286499	1/60
63/0.03	PF6-63/2/003	286500	1/60
63/0.10	PF6-63/2/01	286501	1/60
63/0.30	PF6-63/2/03	286502	1/60
63/0.50	PF6-63/2/05	286503	1/60
<b>4-polni</b>			
25/0.03	PF6-25/4/003	286504	1/30
25/0.10	PF6-25/4/01	286505	1/30
25/0.30	PF6-25/4/03	286506	1/30
25/0.50	PF6-25/4/05	286507	1/30
40/0.03	PF6-40/4/003	286508	1/30
40/0.10	PF6-40/4/01	286509	1/30
40/0.30	PF6-40/4/03	286510	1/30
40/0.50	PF6-40/4/05	286511	1/30
63/0.03	PF6-63/4/003	286512	1/30
63/0.10	PF6-63/4/01	286513	1/30
63/0.30	PF6-63/4/03	286514	1/30
63/0.50	PF6-63/4/05	286515	1/30